





CERAMIC TOILET SUITE



Ceramic wall faced toilet suite Clean Flush, Nanoglaze, Easy Care Height

- Stylish minimalist design with curved pan, sits flat against wall
- Clean Flush rimless pan design for an efficient, powerful flush Easy care height, pan height 440 mm
- White vitreous china with nanoglaze surface, easy to clean
- Soft-closing, easy-clean quick release seat with stainless steel pins
- S or P trap
- Universal cistern, suits back entry or bottom entry plumbing

ORDER CODE	191777	Limni WF, Deluxe seat	Old code: STO-309-04
	191776	Limni WF, Slim seat	Old code: STO-309-02
	191840	Limni WF, Flat seat	Old code: n/a
	191775	Limni WF, Classic seat	Old code: STO-309-00

Universal, suits back entry inlet or bottom entry plumbing. Left and CISTERN

right bottom entry inlet points.

Wall faced close coupled with rimless pan design. PAN Universal trap, suitable for S or P trap installations. TRAPS Quick release seat with stainless steel hinges, soft closing. SEAT

4 star rating 4.5/3 litre water saving flush. WELS

Variable 90-180 using supplied connector; 150mm recommended. SETOUT This is a close coupled toilet suite — the cistern is fixed directly to the FIXING

pan and does not require wall fixing.

Pan may be bedded with cement base or using silicone sealant.

SEAT OPTIONS ᆸ



DELUXE SEAT (40mm lid)

- Premium quality
- Easy to clean, anti-scratch
- Rigid, ceramic-like surface
- Made from Thermoset (UF)

SLIM SEAT (20mm lid)


- Premium quality
- Easy to clean, anti-scratch
- Rigid, ceramic-like surface
- Made from Thermoset (UF)


FLAT SEAT


- Premium quality
- Easy to clean, anti-scratch
- Rigid, ceramic-like surface - Made from Thermoset (UF)

CLASSIC SEAT (40mm lid)

- Lightweight, shiny finish
- Easy to clean
- Rigid, ceramic-like surface
- Made from Thermoplastic (PP)









🌀 Rimless Clean Flush pan – for an efficient, powerful flush. 🕟 Nanoglaze surface – ultra-smooth, anti-bacterial, easy to clean. 庵 Easy care height – making it easier to get on and off the seat.





Please note

- Installation shall be in accordance with AS/NZS3500.
- All measurements are in millimetres. Height dimensions are to base of pan. Make allowance for bedding.
- Bedding: Pan may be bedded with cement base or using silicone sealant. Fix pan to floor using a sand cement mixture of 3:1 to a depth of 60mm. Do not use lime or fast-drying cement.
- Bracket fixing: The pan should be bedded with silicone sealant and fixed with the brackets supplied.
- Do NOT use epoxy type adhesives. Dimensions are nominal and subject to normal ceramic manufacturing variations.
- Specifications may vary without notice as part of our continuous improvement practices.
- Clean with a damp cloth. Do not use abrasive cleaners, liquids or pastes.

bathroom | kitchen | laundry