

90cm Slide-out Rangehood

MODEL / ASL90DR2S

FEATURES

440m³/hr extraction
LED lighting
Aluminium grease filters
Ducted or recirculating installation options
Stainless steel fascia included
2 speed settings

PERFORMANCE FEATURES

440 m³/hr extraction
Motor type:
> Centrifugal
Decibel rating (dBA) max:
> 49-65 dBA

ACCESSORIES

120mm Flue outlet adapter
2 Fascia rails included:
> 40mm for ducted installation
> 80mm for recirculating installation

OPTIONAL ACCESSORIES

Carbon Filter - CP120

PERFORMANCE FEATURES

440 m³/hr extraction
Motor type:
> Centrifugal
Decibel rating (dBA) max:
> 49-65 dBA

CLEANING

Dishwasher safe aluminium grease filters

EAN

9349260002609

PRODUCT DIMENSIONS

Packaged (w, d, h mm)
> 945 × 225 × 360mm
Physical (w, d, h mm)
> 899 × 278-472 × 176mm
Weight (Gross/Net)
> 10.5/9kg

REQUIREMENTS

Supplied with 10 amp plug
Rated voltage:
> 220-240V, 50/60 Hz

INSTALLATION

See below diagram



ALL INALTO PRODUCTS COME WITH A 2 YEAR WARRANTY. AUSTRALIAN CUSTOMERS ARE ELIGIBLE TO RECEIVE 1 EXTRA YEAR FOR FREE, SIMPLY REGISTER ONLINE WITHIN 90 DAYS OF PURCHASE

WWW.INALTO.HOUSE/REGISTRATION

