

52cm Undermount RANGEHOOD

PRODUCT CODE: **EM52UMS**



FEATURES:

- + 430 Grade S/Steel
- + 3 speed motor
- + 550m³/hr extraction capacity
- + 2 x 1.5w LED lights
- + Aluminum mesh washable grease filter
- + Dishwasher safe filters
- + 150mm Airflow outlet
- + Undermount button control
- + Undermount non-visible

3 SPEED MOTOR

This rangehood provides the option of 3 different speed levels ensuring you have the option to use your rangehood at a low, medium or high level of operation.

HIGH EXTRACTION CAPACITY

The extraction capacity of 550m³/hr provides strength and power to this stylish rangehood.

COMMERCIAL STYLE BAFFLE FILTERS

Easy clean, stainless steel baffle filters, are designed to capture all steam and moisture, whilst removing exhaust and odours from the kitchen. Perfect for use over fast heat up cooktops, like induction.

DECIBEL RATING

67 dBA

Electrical Requirements

Rangehood is supplied with 10amp cord & plug.

Decibel Rating

67 dBA

Available Ventilation Kits

- RHKE65EU Wall – Eave vent kit
- RHKMR65EU Universal metal roof kit (includes flashing)
- RHKTR65EU Universal tile roof kit (includes flashing)

Carbon Filter

CFMEM (requires 2)

Barcode

9347726027357



eurocooking



Warranty

HELPFUL TIPS

- + Leave your rangehood on for 15 minutes after the cooking of the food to remove all odors, steam etc.
- + The dishwasher-safe baffle filters need to be cleaned after approximately 2 months of standard operation
- + It is recommended that the rangehood be installed between 650mm and 750mm above the cooktop
- + It is also recommended that fumes from the rangehood be ducted out into the atmosphere.
- + Turn off the rangehood before attempting to clean

INSTALLATION

Installation is recommended by a qualified installer, please refer to the product manual for full installation instructions.

FILTER CLEANING INFORMATION

Cassette mesh filter: Requires cleaning monthly. This will ensure no interruptions with airflow operation.

