70cm Undermount **RANGEHOOD**

PRODUCT CODE: EP70UMS2



FEATURES:

- 430 Grade Stainless Steel Bottom
- 3 Speed Air Function
- 700m3/h Extraction capacity
- 2 x 1.5w LED Light
- Separate Light Function

- Decibel rating 48-58 dBA
- 150mm flue diameter

FLUSH UNDERMOUNT INSTALLATION

This model once installed into the cabinet will sit flush which conceals the remainder of the rangehood, providing a clean and modern look for your rangehood.

SOFT TOUCH UNDERMOUNT CONTROLS

This rangehood provides a Soft Touch Button system designed for easy usage.

The extraction capacity of 700m3/hr provides strength and power to this stylish rangehood.

DISHWASHER SAFE CASSETTE FILTERS

The cassette filters can be placed in a dishwasher for easy cleaning and can easily be removed, re-connected from the rangehood.

HIGH EXTRACTION CAPACITY

instructions.

Cassette mesh filter: Requires cleaning monthly. This will ensure no interruptions with airflow operation.

Barcode	9347726027944
Carbon Filter	CF110 (requires 2)
Available Ventilation Kits RHKE65EU RHKMR65EU RHKTR65EU	Wall – Eave vent kit Universal metal roof kit (includes flashing) Universal tile roof kit (includes flashing)
Decibel Rating	48-58 dBA
Electrical Requirements	Rangehood is supplied with 10amp cord & plug.





HELPFUL TIPS

- Leave your rangehood on for 15 minutes after the cooking of the food to remove all odors, steam etc
- The dishwasher-safe cassette filters need to be cleaned after approximately 2 months of standard operation
- It is recommended that the rangehood be installed between 650mm and 750mm above the cooktop
- It is also recommended that fumes from the rangehood be ducted out into the atmosphere.
- Turn off the rangehood before attempting to

INSTALLATION

Installation is recommended by a qualified installer, please refer to the product manual for full installation

FILTER CLEANING INFORMATION

