# 85cm Undermount Rangehood

# **RANGEHOOD**

PRODUCT CODE: ERH85UMS






## **FEATURES:**

- + 430 grade Stainless steel finish
- + 3 speed motor
- + 1000m<sup>3</sup> / hr extraction capacity
- + 2 x 1.5W LED lights
- + 2 x baffle filters

- Undermount non-visible rangehood
- + Under push button control
- + Dishwasher safe cassette filter
- + Decibel rating 61-65-68 dBA
- 150mm Flue diameter



# 3 SPEED MOTOR

This range hood provides the option of 3 different speed levels ensuring you have the option to use your range hood at a low, medium or high level of operation.

#### EXTRACTION CAPACITY

The extraction capacity of  $1000 \, \text{m}^3$  / hr provides strength and power to this stylish range hood.

# DISHWASHER SAFE CASSETTE FILTERS

The cassette filter has 5 aluminum layers, it can be placed in a dishwasher for easy cleaning and can easily be removed and re-connected from the range hood.

#### FILTER CLEANING INFORMATION

Cassette filter requires cleaning monthly.

This will ensure no interruptions with airflow operation.

# SPECIFICATIONS:

Electrical Requirements	Rangehood is supplied with 10amp cord & plug.
Decibel Rating	61-65-68 dBA
Available Ventilation Kits	
RHKE65EU	Wall – Eave vent kit
RHKMR65EU	Universal metal roof kit (includes flashing)
RHKTR65EU	Universal tile roof kit (includes flashing)
Product Dimensions	<b>W</b> 850mm × <b>D</b> 290mm

### **HELPFUL TIPS**

- Leave your range hood on for 15 minutes after the cooking of the food to remove all odors, steam etc.
- The dishwasher-safe cassette filters need to be cleaned after approximately 2 months of standard operation
- + It is recommended the range hood be installed between 650mm and 750mm above the cook top
- + It is also recommended that fumes from the range hood be ducted out into the atmosphere.
- + Turn off the range hood before attempting to clean

### INSTALLATION

Installation is recommended by a qualified installer, please refer to the product manual for full installation instructions.