



# GMF6422IXL

## 60CM 4 BURNER GAS COOKTOP



### FEATURES & BENEFITS



#### IXLIUM

Whirlpool introduces an innovative material aimed at all those who love design, but hate cleaning. Thanks to an exclusive nano-technology treatment, the iXelium cooktop is extremely easy to clean. Unlike a standard steel top, iXelium prevents food residuals from sticking to the surface so all you need to do to remove dirt is a soft sponge and non aggressive detergent. The result is a cooking surface which will remain shiny over time without scratches.



#### HIGH EFFICIENCY BURNERS

This model features 5 unique vertical flame burners that enable fast cooking, while at the same time decreasing energy consumption and CO2 emissions.



#### POWERFUL RAPID BURNER

Whirlpool's high powered rapid burner is included for extra strength cooking.



#### CAST IRON TRIVETS & WOK SUPPORT

Traditional Cast Iron for a premium finish, durability and long lasting quality features, including Wok Support.



#### LASER ETCHED SERIGRAPHY

The sleek design includes laser etched serigraphy on control panel settings and logo.



#### WARRANTY

Guarantees peace of mind and value for money knowing that any product fault or defect is covered by full replacement parts and/or a service call to ensure the product works as described.

### TECHNICAL SPECIFICATIONS

MAIN COLOUR FINISH	Stainless Steel Ixelium
PRODUCT DIMENSIONS	W 590mm x H 41mm x D 510mm
CUT OUT DIMENSIONS	W 560mm x H 38mm x D 480mm
PACKAGE DIMENSIONS	W 670mm x H 155mm x D 595mm
BURNERS	4, Black
CONTROLS	4 Front Knobs
TRIVETS	2 Cast Iron
IGNITION	Electric
SAFETY	Flame Failure
ELECTRICAL RATING	10amps
ELECTRICAL CONNECTION	Plug and Supplied
INSTALLATION	Built-In
NET WEIGHT	10.5kg
ACCESSORIES INCLUDED	LPG Jets Included, Cast Iron Trivets and wok support
WARRANTY	5 years

### BURNER SPECIFICATIONS

FRONT RHS: POT SIZE: NPG: Pressure, Injector & Rate ULPG: Pressure, Injector & Rate	Auxiliary 8cm to 14cm 1.00kPa, 0.90mm & 3.60Mj/h 2.75kPa, 0.52mm & 3.60Mj/h
REAR RHS: POT SIZE: NPG: Pressure, Injector & Rate ULPG: Pressure, Injector & Rate	Semi-Rapid 16cm to 22cm 1.00kPa, 1.17mm & 6.30Mj/h 2.75kPa, 0.67mm & 6.30Mj/h
REAR LHS: POT SIZE: NPG: Pressure, Injector & Rate ULPG: Pressure, Injector & Rate	Semi-Rapid 16cm to 22cm 1.00kPa, 1.17mm & 6.30Mj/h 2.75kPa, 0.67mm & 6.30Mj/h
FRONT LHS: POT SIZE: NPG: Pressure, Injector & Rate ULPG: Pressure, Injector & Rate	2 Crown 24cm to 26cm 1.00kPa, 1.92mm & 17.28Mj/h 2.75kPa, 1.08mm & 17.28Mj/h

DISTRIBUTED BY ARISIT PTY LTD

40-50 Mark Anthony Drive, Dandenong South VIC 3175  
Ph: 1300 762 219 Fax: 03 9768 0838 Website: www.arisit.com